

2. TFI ISO/API Tubing Products Catalogue

1	Labels		Outside diameter	Nominal linear masses		Wall thickness	Type of end-finish				
	2			Non-upset T&C	Ext. upset T&C		H40	J55	L80	N80 Type 1,Q	P110
	NU T&C	EU T&C	D mm	kg/m	kg/m	t mm					
1	2	3	4	5	6	7	8	9	10	11	12
2-3/8	4	—	60.32	5.95	—	4.24	N	N	N	N	—
2-3/8	4.6	4.7	60.32	6.85	6.99	4.83	NU	NU	NU	NU	NU
2-3/8	5.8	5.95	60.32	8.63	8.85	6.45	—	—	NU	NU	NU
2-3/8	7.35	7.45	60.32	10.94	11.09	8.53	—	—	U	—	—
2-7/8	6.4	6.5	73.02	9.52	9.67	5.51	NU	NU	NU	NU	NU
2-7/8	7.8	7.9	73.02	11.61	11.76	7.01	—	—	NU	NU	NU
2-7/8	8.6	8.7	73.02	12.8	12.95	7.82	—	—	NU	NU	NU
2-7/8	9.35	9.45	73.02	13.91	14.06	8.64	—	—	U	—	—
3-1/2	7.7	—	88.9	11.46	—	5.49	N	N	N	N	—
3-1/2	9.2	9.3	88.9	13.69	13.84	6.45	NU	NU	NU	NU	NU
3-1/2	10.2	—	88.9	15.18	—	7.34	N	N	N	N	—
3-1/2	12.7	12.95	88.9	18.9	19.27	9.52	—	—	NU	NU	NU
4	9.5	—	101.6	14.14	—	5.74	N	N	N	N	—
4	10.7	11	101.6	—	16.37	6.65	U	U	U	U	—
4-1/2	12.6	12.75	114.3	18.75	18.97	6.88	NU	NU	NU	NU	—

N = Non-upset threaded and coupled, U = External upset threaded and coupled